


RecoverXLT2-AP™ Refrigerant Recovery System



YELLOW JACKET®



Features

- 1/2 hp, twin cylinder, oil-less compressor for fast recovery of Class III, IV and V refrigerants including R-32, R-1234yf and R-1234ze.
- Safe venting of case interior prior to start up.
- Low pressure switch stops recovery above ambient pressure for leaking systems to prevent pulling air into recovery cylinders.
- Low pressure bypass for recovery of leak-free systems. Patented single valve control for easy changeover from liquid to vapor to purge.
- Auto purge clears residual refrigerant for quick change from one refrigerant to another.
- Condenser with gravity drain keeps recovery tank up to 10° cooler for reliable operation in high ambient conditions.
- Lightweight case designed for easy carrying.
- One year warranty.
- Designed and manufactured in the U.S.A. 

Specifications:

Capabilities:	Vapor, liquid, push/pull
Refrigerants:	R-32, R-1234yf, R-1234ze as well as the most common CFC, HFC and HFO refrigerants, including R-22, R-404A, R-407, R-410A, R-448A and R-449A
Compressor:	½ hp, twin cylinder, reciprocating, oil-less
Power Source:	230V - 50/60 Hz
Amps:	4.0
High Pressure Shut-Off:	517 psig/35 bar – auto reset
Operating Temperature:	40° to 122° F (4° to 50° C)
Weight:	14.5 kg/32 lbs.
Dimensions:	19.3(w) x 12.4 (h) x 12.5 (d) in. 490 (w) x 315 (h) x 317 (d) mm

Designed to Meet Safety Requirements for R-32, R-1234yf and R-1234ze

The drive to lower global warming potential refrigerants with increased flammability has necessitated the evolution of the market leading YELLOW JACKET® RecoverXLT™ recovery machine: The new RecoverXLT2-AP™ Refrigerant Recovery Machine with twin cylinder 1/2 hp oil less compressor and gravity drain condenser. The unique “ambient pressure switch” and three meter power cord comply with the current safety requirements. The RecoverXLT2-AP is specifically designed for the new lower GWP refrigerants including R-32, R-1234yf and R-1234ze as well as the most common CFC, HFC and HFO refrigerants, including R-22, R-404A, R-407, R-410A, R-448A and R-449A.

Set yourself up to work smart. Surround yourself with the hardest working, highest performing tools available. The YELLOW JACKET RecoverXLT2-AP and other YELLOW JACKET service tools for the HVAC/R service professional.

	Calculated Recovery Ratings					
	Kg./min			Kg./hour		
	Vapor	Push/Pull	Liquid	Vapor	Push/Pull	Liquid
R-22	0.17	4.16	3.10	10	250	186
R-32	0.11	3.41	2.53	7	205	152
R-134a	0.20	4.20	3.14	12	252	188
R-404A	0.30	3.66	2.73	18	220	164
R-410A	0.18	3.7	2.77	11	222	166
R-1234yf	0.17	3.83	2.86	10	230	171
R-407C	0.18	3.99	2.98	11	240	179

UPC #	Description
95764	RecoverXLT2-AP™ Refrigerant Recovery System 230V/50-60 Hz (Euro, UK, NZ and Australian plug)

Ritchie Engineering Co., Inc.
YELLOW JACKET Products Division
10950 Hampshire Avenue South
Bloomington, MN 55438-2623 USA
Phone: (800)769-8370 or (952)943-1333
e-mail: custserv@yellowjacket.com
www.yellowjacket.com



P/N 10140