

Life Is On



# D Controls

Adjustable temperature and pressure controls

High-quality & great reliability thanks to Eliwell's application knowledge combined with 30-year expertise in marketing Ranco products

[www.eliwell.com](http://www.eliwell.com)

**Download My Eliwell APP!**



It is the solution to find in real time any information on hundreds of Eliwell products for refrigeration and HVAC systems.

# D Controls

## Adjustable temperature and pressure controls

### D16T - Temperature

		TEMPERATURE RANGES			
		-20...+15 °C -4...+59 °F	-10...+25 °C +14...+77 °F	-40...-5 °C -40...+23 °F	+5...+40 °C +41...+104 °F
SENSING ELEMENT	STRAIGHT CAPILLARY	R automatic D adjustable L 2-3-6-12 m	R automatic D adjustable L 2-3 m	R automatic D adjustable L 2 m	—
	COILED END	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	—
	BULB	R automatic D adjustable L 2 m	R automatic D adjustable L 2 m	—	R automatic D adjustable L 2 m
	AMBIENT (CAGE)	R automatic D adjustable	R automatic D adjustable	—	R automatic D adjustable

R = Reset D = Differential L = Sensing element length

### D16P - Single pressure

		PRESSURE RANGES			
		LP -0,3...7 bar -0,4...100 psi	HP 7...31 bar 100...450 psi	HP 10...45 bar 145...650 psi	FAN 7...20 bar 100...290 psi
FITTING	7/16-20 MALE	R automatic D adjustable	R automatic D adjustable	R automatic D adjustable	R automatic D adjustable
	7/16	R manual D fixed	R manual D fixed	R manual D fixed	—
	1m with flare 7/16	R automatic D adjustable	R automatic D adjustable	—	R automatic D adjustable
	CAPILL. 1m with flare 7/16	R manual D fixed	R manual D fixed	—	—

R = Reset D = Differential

### D17P - Dual pressure

		PRESSURE RANGES			
		LP -0,3...7 bar LP -0,4...100 psi	HP 7...31 bar HP 100...450 psi	LP -0,3...7 bar LP -0,4...100 psi	HP 10...45 bar HP 145...650 psi
FITTING	7/16-20 MALE	R automatic D adjustable	R automatic D fixed	R automatic D adjustable	R automatic D fixed
		R automatic D adjustable	R manual D fixed	—	—
		R manual D fixed	R manual D fixed	R manual D fixed	R manual D fixed
	CAPILL. 1m with flare 7/16	R automatic D adjustable	R automatic D fixed	—	—
		R automatic D adjustable	R manual D fixed	—	—
		R manual D fixed	R manual D fixed	—	—

R = Reset D = Differential

### Available accessories



CT123407 • TDS D CONTROLS • EN • rel.12/18 • © Eliwell Controls s.r.l. 2018 - All rights reserved

### ITALY - Headquarters

Eliwell Controls srl  
Via dell'Industria, 15 Z.I. Paludi  
32016 Alpagno (BL) - ITALY  
T: +39 0437 986 111  
F: +39 0437 989 066

Follow us on

Sales  
T: +39 0437 986 100 (Italy)  
T: +39 0437 986 200 (other countries)  
E: saleseliwell@schneider-electric.com

Technical support  
T: +39 0437 986 300  
E: techsuppeliwell@schneider-electric.com

[www.eliwell.com](http://www.eliwell.com)

### Download My Eliwell APP!



It is the solution to find in real time any information on hundreds of Eliwell products for refrigeration and HVAC systems.