

2650 - 17050 W

New



4 = 4.5 mm Passo alette Fin spacing			TC > -25 °C						
Modello	Type	F31HC	115-4	116-4	125-4	126-4	135-4	136-4	146-4
Potenza (R404A)	● TC 2,5 °C (ΔT1 10K) W		3400	4200	6950	8400	10300	12900	17050
Capacity	TC 0 °C (ΔT1 8K) W		2530	3100	5100	6200	7600	9500	12550
Portata d'aria	Air quantity	m ³ /h	1.600	1.400	3.200	2.800	4.800	4.200	5.600
Freccia d'aria	Air throw	m	17	15	20	18	24	21	22
Superficie esterna	External surface	m ²	8,9	13,3	17,8	26,6	26,7	39,9	53,2
Superficie interna	Internal surface	m ²	0,5	0,8	1,1	1,6	1,6	2,4	3,2
Peso	Weight	kg	23	25	39	44	56	63	82
6 = 6.0 mm Passo alette Fin spacing			TC > -25 °C						
Modello	Type	F31HC	215-6	216-6	225-6	226-6	235-6	236-6	246-6
Potenza (R404A)	● TC 2,5 °C (ΔT1 10K) W		2950	3800	6000	7600	8950	11500	15350
Capacity	TC 0 °C (ΔT1 8K) W		2180	2800	4400	5600	6600	8450	11300
Portata d'aria	Air quantity	m ³ /h	1700	1500	3400	3000	5100	4500	6000
Freccia d'aria	Air throw	m	19	16	22	19	25	22	23
Superficie esterna	External surface	m ²	6,8	10,2	13,6	20,4	20,4	30,6	40,8
Superficie interna	Internal surface	m ²	0,5	0,8	1,1	1,6	1,6	2,4	3,2
Peso	Weight	kg	22	24	38	42	54	60	78
7 = 7.0 mm Passo alette Fin spacing			TC > -25 °C						
Modello	Type	F31HC	315-7	316-7	325-7	326-7	335-7	336-7	346-7
Potenza (R404A)	● TC 2,5 °C (ΔT1 10K) W		2650	3500	5400	7050	8100	10550	14200
Capacity	TC 0 °C (ΔT1 8K) W		1970	2580	3950	5150	5950	7750	10450
Portata d'aria	Air quantity	m ³ /h	1750	1600	3500	3200	5250	4800	6400
Freccia d'aria	Air throw	m	20	17	23	20	26	24	25
Superficie esterna	External surface	m ²	5,9	8,9	11,8	17,8	17,7	26,7	35,6
Superficie interna	Internal surface	m ²	0,5	0,8	1,1	1,6	1,6	2,4	3,2
Peso	Weight	kg	21	23	37	41	53	58	76

DATI COMUNI / COMMON DATA									
Elettroventilatori	Fans	Ø 315 mm x n°	1 o	1 o	2 oo	2 oo	3 ooo	3 ooo	4 oooo
Assorbimento motori	Motor power consumption	W	66	66	132	132	198	198	264
		A	0,6	0,6	1,2	1,2	1,8	1,8	2,4
Sbrinamento	Defrost	E 230 V	W	1700	2550	2900	4300	4050	7800
Volume circuito	Circuit volume	dm ³	1,5	2,3	2,8	4,2	4,1	6,3	8,1
Potenza sonora	Sound power level	db (A)	69	69	72	72	74	74	75

(●) Per altre condizioni vedere diagrammi. (●) For other conditions see diagrams.

