

AC axial fan

sickled blades (S series)
with guard grille for short nozzle



ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

County court Stuttgart · HRB 590142



Nominal data

| | | | | | |
|-------------------------------|-------------------|------|------|------|------|
| Type | S4D400-AP12-50 | | | | |
| Motor | M4D074-EI | | | | |
| Phase | | 3~ | 3~ | 3~ | 3~ |
| Nominal voltage | VAC | 230 | 230 | 400 | 400 |
| Connection | | Δ | Δ | Y | Y |
| Frequency | Hz | 50 | 60 | 50 | 60 |
| Type of data definition | | fa | fa | fa | fa |
| Valid for approval / standard | | CE | CE | CE | CE |
| Speed | min ⁻¹ | 1450 | 1690 | 1450 | 1690 |
| Power input | W | 135 | 185 | 135 | 185 |
| Current draw | A | 0.76 | 0.68 | 0.44 | 0.39 |
| Max. back pressure | Pa | 150 | 120 | 150 | 120 |
| Min. ambient temperature | °C | -25 | -25 | -25 | -25 |
| Max. ambient temperature | °C | 40 | 40 | 40 | 40 |
| Starting current | A | 3.0 | 3.0 | 1.7 | 1.7 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

| | |
|-----------------------|--------|
| Installation category | A |
| Efficiency category | Static |
| Variable speed drive | No |
| Specific ratio* | 1.00 |

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

| | | Actual | Request 2013 | Request 2015 |
|--------------------------------|-------------------|--------|--------------|--------------|
| Overall efficiency η_{es} | % | 32.7 | 25.1 | 29.1 |
| Efficiency grade N | | 43.6 | 36 | 40 |
| Power input P_e | kW | 0.19 | | |
| Air flow q_v | m ³ /h | 2595 | | |
| Pressure increase p_{fs} | Pa | 91 | | |
| Speed n | min ⁻¹ | 1415 | | |

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

LU-27622



AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Technical features

| | |
|--|---|
| Mass | 5 kg |
| Size | 400 mm |
| Surface of rotor | Coated in black |
| Material of terminal box | ABS plastic, black |
| Material of blades | Sheet steel, coated in black |
| Number of blades | 5 |
| Direction of air flow | "V" |
| Direction of rotation | Counter-clockwise, seen on rotor |
| Type of protection | IP 44; Depending on installation and position as per EN 60034-5 |
| Insulation class | "B" |
| Humidity class | F1-2 |
| Max. permissible ambient motor temp. (transp./ storage) | + 80 °C |
| Min. permissible ambient motor temp. (transp./storage) | - 40 °C |
| Mounting position | Shaft horizontal or rotor on bottom; rotor on top on request |
| Condensate discharge holes | Rotor-side |
| Operation mode | S1 |
| Motor bearing | Ball bearing |
| Touch current acc. IEC 60990 (measuring network Fig. 4, TN system) | < 0.75 mA |
| Electrical leads | Via terminal box, integrated capacitor connected via terminal box |
| Cable exit | Variable |
| Protection class | I (if protective earth is connected by customer) |
| Product conforming to standard | EN 60335-1; CE |
| Approval | CCC |




AC axial fan

sickled blades (S series)

with guard grille for short nozzle

Product drawing




| | |
|---|--|
| 1 | Direction of air flow "V" |
| 2 | Tightening torque 0.5±0.1 Nm |
| 3 | Cable diameter max. 7.5 mm, tightening torque 1.3±0.2 Nm |

AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Connection screen



| | | | | | |
|----|-------------------|----|-----------------|----|------------------|
| | Three-phase motor | Y | Star connection | Δ | Delta connection |
| L1 | = U1 = blue | L2 | = V1 = black | L3 | = W1 = brown |
| U2 | = white | V2 | = green | W2 | = yellow |
| PE | PE (green/yellow) | | | | |




AC axial fan

sickled blades (S series)

with guard grille for short nozzle

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: L_{wA} measured as per ISO 13347 / L_{pA} measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

| | Conn. | U | f | n | P _e | I | L _{pA_{in}} | L _{wA_{in}} | qv | p _{fs} |
|---|-------|-----|----|-------------------|----------------|------|------------------------------|------------------------------|------|-----------------|
| | | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m³/h | Pa |
| 1 | Y | 400 | 50 | 1450 | 135 | 0.44 | 65 | 74 | 4000 | 0 |
| 2 | Y | 400 | 50 | 1435 | 161 | 0.47 | 65 | 73 | 3535 | 35 |
| 3 | Y | 400 | 50 | 1420 | 182 | 0.49 | 65 | 72 | 2995 | 70 |
| 4 | Y | 400 | 50 | 1410 | 203 | 0.50 | 67 | 74 | 2355 | 100 |


Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side
qv = Air flow · p_{fs} = Pressure increase



AC axial fan

sickled blades (S series)
with guard grille for short nozzle

Charts: Air flow 60 Hz



Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

| | Conn. | U | f | n | P _e | I | LpA _{in} | LwA _{in} | q _v | p _{fs} |
|---|-------|-----|----|-------------------|----------------|------|-------------------|-------------------|-------------------|-----------------|
| | | V | Hz | min ⁻¹ | W | A | dB(A) | dB(A) | m ³ /h | Pa |
| 1 | Y | 400 | 60 | 1690 | 185 | 0.39 | 69 | 76 | 4615 | 0 |
| 2 | Y | 400 | 60 | 1660 | 223 | 0.45 | 70 | 76 | 4145 | 40 |
| 3 | Y | 400 | 60 | 1635 | 256 | 0.49 | 69 | 76 | 3580 | 80 |
| 4 | Y | 400 | 60 | 1605 | 290 | 0.54 | 70 | 76 | 2895 | 120 |

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
q_v = Air flow · p_{fs} = Pressure increase

